




**LOGGIA**  
industria vernici

# TECHNICAL DATA SHEET

Revisione: 7 novembre 2014



## Dorotea

**Wax Acrylic Decor Effect.**

### General Characteristics

<b>Composition:</b>	DOROTEA is decorative coating for indoors with gold and silver metallic effect in fine or coarse grain.
<b>Recommended usage:</b>	For its elegance Dorotea is recommended for protection and decoration of modern and antiques buildings, villas, hotels and offices.

### Preparation

**Surface Preparation:**



Before to apply Dorotea is necessary proceed with surface preparation with powder or paste putties (As Flystuk) shaved properly with sanding paper (grain P120) about 12 hours after its application. Clean the surface after sanding and apply 1 coat of vinyl fixative FISSAMUR tinned with water at 1:3. 4-5 hours after fixative application, apply 2 coat of MAXI FOND (5-6 hours in between ).



### Product Application

**Methods:**

Decorative brush or glave: Ready to use. Can be tinned with water just to obtain more soft effect up to 5%



After 6-8 hours of Primer application, apply first coat of Dorotea crossing the brush strokes in order to distribute the product all over the surface. 4-6 hours later apply second coat in the same way.

Temperature of application	+5 ÷ +35	°C
Humidity of application:	< 85%	
Dry film thickness:	35 ÷ 50	µm per coat
Touch dry:	4 ÷ 6	h
Recoatable after:	12	h
Completely cured:	24	h
Tools cleaning:	with water	

## Colouring

---



This product can be coloured with Tinting system L'ANGELO and L'ANGELO OX. In addition it can be tinted with Universal Strainers to obtain customized shades.

Take care when you use different batches of the same color. Mix them together to ensure color uniformity during the application.

## Technical Properties

---

Density:	1,1 ÷ 1,2	Kg/l
Viscosity:		cPs
pH:	7-8	
Weight Solids:	40%	
Coverage:	7 – 8	mq/l
Colour:	Color Chart	
Gloss Level:	Semi gloss waxed	
Pack size:	0,75 - 4 – 14	l

## Storage

---



Shelf-life: 2 years in original tightly closed containers away from direct sunlight and excessive heat.

The can should be resealed and stored tightly closed to prevent evaporation of the product and entry of air. Store it upside down after use.



Min storage temperature: +5°C

Max storage temperature: +30°C

## Safety Precautions:

---

**For all information regarding product use and correct product disposal please refer to Safety Data Sheet.**

---

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**Company with Certified Quality System by BVQI according to UNI EN ISO 9001:2000.**